



Информационное письмо/Information letter

| model | dimensions in mm (LxWxH) | | | Weight (KG) | Engine type | Engine speed iddling/load | Air end | Rated operating Pressure | F.A.D. (m3/min) | Fuel tank volume (L) | Fuel consum. min - max (L/H) |
|--------|--------------------------|------|------|-------------|---------------------|---------------------------|----------|--------------------------|-----------------|----------------------|------------------------------|
| PDV 15 | 2680 | 1230 | 1200 | 485 | Vanguard 850D | 1900/3200 | B100 | 7 BAR | 2,00 | 21,00 | 1,9 - 4,3 |
| PDP 15 | 2680 | 1230 | 1200 | 495 | Perkins 403-D07 | 1900/3200 | B100 | 7 BAR | 2,00 | 21,00 | 1,8 - 4,1 |
| PDV 20 | 3040 | 1300 | 1295 | 690 | Vanguard 950D | 1900/3400 | B100 | 7 BAR | 2,90 | 35,00 | 2,9 - 6,4 |
| PDP 20 | 3040 | 1300 | 1295 | 690 | Perkins 403-D11 | 1900/3400 | B100 | 7 BAR | 3,00 | 35,00 | 2,6 - 5,9 |
| PDP 28 | 3250 | 1485 | 1220 | 900 | Perkins 404D-22 | 1300/2400 | B100 | 7 BAR | 4,80 | 70,00 | 4,3 - 9,5 |
| | | | | | Perkins 404D-22 | 1300/2400 | B100 | 10 BAR | 3,50 | 70,00 | 4,3 - 9,5 |
| | | | | | Perkins 404D-22 | 1300/2400 | B100 | 12 BAR | 2,90 | 70,00 | 4,3 - 9,5 |
| | | | | | Perkins 404D-22 | 1300/2400 | B100 | 13 BAR | 2,60 | 70,00 | 4,3 - 9,5 |
| PD 51 | 3528 | 1490 | 1334 | 1000 | Cummins A2300 | n/a | EK123 NG | 7 BAR | 5,00 | 60,00 | 4,4 - 9,8 |
| PD 71 | 3792 | 1580 | 1390 | 1300 | Cummins A2011 | n/a | EK123 NG | 7 BAR | 7,60 | 120,00 | 6,5 - 17 |
| PDP 90 | 4000 | 1960 | 1900 | 2100 | Perkins 1104D-E44TA | 1300/1800 | SCA 14DR | 7 BAR | 10,20 | 190,00 | 12,5 - 18,5 |
| | | | | | Perkins 1104D-E44TA | 1300/1800 | SCA 14DR | 10 BAR | 9,20 | 190,00 | 12,5 - 18,5 |
| | | | | | Perkins 1104D-E44TA | 1300/1800 | SCA 14DR | 12 BAR | 8,20 | 190,00 | 12,5 - 18,5 |

Президент компании/President of the company
Вит Линхарт/Vit Linhart