

Характеристики спиральных  
компрессоров "OF Kompressoren"  
2014 год.

Модель	Производительность, л/мин		Осушитель	Ресивер, л	Прсоед.	Уровень шума, дБ(А)	Габариты, мм
	8 бар	10 бар					
OF 1,5	160	-	-	-	G 1/2	52 / -	910x550x920
OF 2,2	238	195	-	-	G 1/2	55 / 53	910x550x920
OF 3,7	397	-	-	-	G 1/2	54 / -	910x550x920
OF 4,5	-	405	-	-	G 1/2	- / 54	910x550x920
OF 5,5	627	520	-	-	G 1/2	59 / 57	910x550x920
OF 7,5	794	-	-	-	G 1	58 / -	1400x920x1020
OF 9,0	-	810	-	-	G 1	- / 59	1400x920x1020
OF 11,0	1254	1040	-	-	G 1	61 / 60	1400x920x1020
OF 13,5	-	1215	-	-	G 1	- / 62	1400x920x1890
OF 15	1780	-	-	-	G 1	65 / -	1400x920x1020
OF 16,5	1880	1560	-	-	G 1	64 / 63	1400x920x1890
OF 22	2510	2080	-	-	G 1	66 / 65	1400x920x1890
OF 22,5	2670	-	-	-	G 1	68 / -	1400x920x1890
OF 30	3560	-	-	-	G 1	71 / -	1400x920x1890
OFR 1,5	160	-	-	90*	G 1/2	52 / -	1224x550x1390
OFR 2,2	238	195	-	90*	G 1/2	55 / 53	1224x550x1390
OFR 3,7	397	-	-	250**	G 1/2	54 / -	1410x570x1550
OFR 4,5	-	405	-	250**	G 1/2	- / 54	1410x570x1550
OFR 5,5	627	520	-	250**	G 1/2	59 / 57	1410x570x1550
OFR 7,5	794	-	-	500	G 1	58 / -	1670x920x1811
OFR 9,0	-	810	-	500	G 1	- / 59	1670x920x1811
OFR 11,0	1254	1040	-	500	G 1	61 / 60	1670x920x1811
OFT 1,5	160	-	+3 оС	-	G 1/2	52 / -	1165x550x920
OFT 2,2	238	195	+3 оС	-	G 1/2	55 / 53	1165x550x920
OFT 3,7	397	-	+3 оС	-	G 1/2	54 / -	1165x550x920
OFT 4,5	-	405	+3 оС	-	G 1/2	- / 54	1165x550x920
OFT 5,5	627	520	+3 оС	-	G 1/2	59 / 57	1165x550x920
OFT 7,5	794	-	+3 оС	-	G 1	58 / -	1400x920x1020
OFT 9,0	-	810	+3 оС	-	G 1	- / 59	1400x920x1020
OFT 11,0	1254	1040	+3 оС	-	G 1	61 / 60	1400x920x1020
OFT 13,5	-	1215	+3 оС	-	G 1	- / 62	1400x920x1890
OFT 16,5	1880	1560	+3 оС	-	G 1	64 / 63	1400x920x1890
OFT 22	2510	2080	+3 оС	-	G 1	66 / 65	1400x920x1890
OFTR 1,5	160	-	+3 оС	90*	G 1/2	52 / -	1224x550x1390
OFTR 2,2	238	195	+3 оС	90*	G 1/2	55 / 53	1224x550x1390
OFTR 3,7	397	-	+3 оС	250**	G 1/2	54 / -	1410x570x1550
OFTR 4,5	-	405	+3 оС	250**	G 1/2	- / 54	1410x570x1550
OFTR 5,5	627	520	+3 оС	250**	G 1/2	59 / 57	1410x570x1550
OFTR 7,5	794	-	+3 оС	500	G 1	58 / -	1670x920x1811
OFTR 9,0	-	810	+3 оС	500	G 1	- / 59	1670x920x1811
OFTR 11,0	1254	1040	+3 оС	500	G 1	61 / 60	1670x920x1811

Данные на компрессоры серий OFA и OFRA (с адсорбционным осушителем) по запросу.